

Innovative by tradition.

MAYSER[®]

Innovative by tradition.

www.mayser.com

Mayser USA, Inc.

6200 Schooner Drive 48111 Belleville / Michigan USA

Phone: +1 734 858-1290 usa@mayser.com

Mayser GmbH & Co. KG

Bismarckstrasse 2 88161 Lindenberg GERMANY

Phone: +49 8381 507-0 info.lindenberg@mayser.com

Mayser France

Les Aunettes 12M Bd. Louise Michel 91030 Evry Cedex FRANCE

Phone: +33 1 6077-3637 france@mayser.com

Mayser GmbH & Co. KG

Oerlinger Strasse 1–3 89073 Ulm GERMANY

Phone: +49 731 2061-0 info.ulm@mayser.com

Mayser Slovakia s.r.o.

Gemerska 564 04951 Brzotin SLOVAKIA

Phone: +421 58-7884870 roznava@mayser.com

Mayser Kunshan Co., Ltd.

梅斯安全部件(昆山)有限公司 No. 329, Jujin Road, Zhangpu Township, 215321 Kunshan CHINA

china@mayser.com



Foam Solution

Sacrifice mat

The sacrifice mat from the foam expert

For the past four decades, Mayser has successfully supplied the market with custom polyurethane foam and foam molding technology.

Mayser serves many industries including the automotive, medical, industrial, robotic, aerospace, and commercial vehicle industry.

Innovative thinking and flexibility are our strengths. This is what enables us to develop individual and creative foam solutions for our customers. Other success factors include our broad industry-specific know-how, fast development processes, and competent technical advice.

INDUCON® is the perfect solution for your sacrifice mat needs. Whether you use vacuum, flatbed, or vertical milling machines, INDUCON helps facilitate accurate, effective, and safe cutting. INDUCON's air permeability allows for sufficient and consistent suction from your vacuum to your material. Different mat thicknesses provide the perfect solution for suction requirements as well as table protection. INDUCON can also be equipped with an air permeable adhesive to support vertical cutting tables or cutting small materials by creating additional stability between table and material.



Technical data

	INDUCON S 230 in 1.0 mm	INDUCON S 230 in 2.0 mm	INDUCON S/C 230 GRIP in 1.0 mm
Basis	Polyurethane ester	Polyurethane ester	Polyurethane ester, equipped with an air-permeable acrylate adhesive coating on one side
Thickness	1.0 ± 0.1 mm	2.0 ± 0.1 mm	1.0 ± 0.1 mm
Density	230 kg/m³	230 kg/m³	270 kg/m³
Part number	2000084	2000035	2003163
Porosity	mixed cell	mixed cell	mixed cell
	(approx. 85 % open pores)	(approx. 85 % open pores)	(approx. 85 % open pores)
Color	dark gray	dark gray	dark gray
Delivery form	rolls (sleeve 76 mm) thickness: from 1.0 to 5.0 mm width: 1,030 to 1,530 mm (on request) length: roll starting at 60 per rm and a multiple thereof plates on request	rolls (sleeve 76 mm) thickness: from 1.0 to 5.0 mm width: 1,030 to 1,530 mm (on request) length: roll starting at 60 per rm and a multiple thereof plates on request	rolls (sleeve 76 mm) width: 1,000 to 1,500 mm (on request) length: 120, 240 rm
Options	Your company logo or name printed on the sacrifice mats.		
Sample			